



PRODUCT FEATURES:

- **Touchless operation** limits the spread of germs for a safer restroom.
- **Flexible Selectronic Platform** with programmable, multi-function sensor.
- **Easy & Flexible Installation:** 3-hole, 4" centerset installation. Water resistant solenoid enclosure mounts to wall.
- **Durable Vandal-Resistant Cast Body:** Ideal for high-use commercial applications.
- **Self-Cleaning Solenoid Valve:** Wiper spring prevents clogging
- **Easy to Service Integrated Strainer:** Patented integrated strainer protects solenoid from debris. Strainer is enclosed in removable debris cup for easy service.
- **Optional Auto Purge Feature:** Faucet can be programmed to open at a pre-determined time after the last use to purge the faucet and water lines of stagnant water.
- **Safety Timer:** Helps prevent vandalism by turning off the faucet if the sensor is covered for more than 1 minute. Timing is adjustable with optional remote control.
- **Adjustable Range:** Detection zone can be adjusted manually or with optional remote control.
- **Fail-Safe:** Faucet automatically shuts off upon loss of power or dead battery. Prevents costly excess water usage and potential flooding.
- **Low Lead:** Faucet contains ≤ 0.25% total lead content by weighted average.

MODEL NUMBER:

■ **DC (CR-P2 LITHIUM BATTERY) POWERED**

- **6055.205** 0.5 gpm/1.9 L/min pressure compensating, vandal-resistant multi-laminar spray.
- **6055.204** 0.35 gpm/1.3 L/min pressure compensating, vandal-resistant multi-laminar spray. Faucet is factory set for 7.5 second running time to deliver 0.044 g/0.17 L per cycle.
- **6055.202** 1.5 gpm/5.7 L/min pressure compensating, vandal-resistant aerator.



■ **OPTIONAL Mixing Valve**

- **605XTMV1070** Thermostatic mixing valve. 20" flexible inlet hoses with 3/8" compression fittings. ASSE 1070 certified down to 0.35 gpm/1.3 L/min.

- **DC (Battery):** CR-P2 lithium battery. Battery Life - 192,000 cycles (4 years @ 4,000 cycles per month).

GENERAL DESCRIPTION:

Electronic faucet with proximity operation. 4" centerset with vandal-resistant cast construction. Water pressure range from 20 to 125 psi. Single inlet. 18" flexible inlet hose with 3/8" compression fitting for connection to control box.

RECOMMENDED SPECIFICATION:

Electronic, sensor-operated lavatory faucet shall feature a programmable, multi-function sensor and an electronically operated self-cleaning solenoid valve. Shall also feature a vandal resistant cast centerset construction with single inlet and in-line strainer. Shall meet ANSI A112.18.1 and ANSI 117.1 codes. Fitting shall be American Standard Model # 6055_20_.

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

- ANSI A117. 1**
- ASME A112.18.1**
- CSA B125.1**
- NSF 61/Section 9**
- NSF 372**

