




# SELECTRONIC™ EXPOSED 1.0 GPF URINAL FLUSH VALVE HARD-WIRED AC POWERED, SENSOR OPERATED



## GENERAL DESCRIPTION:

Exposed, Hard-wired AC Powered, Sensor Operated Selectronic™ Urinal Flush Valve for 3/4" top spud urinals.

Inlet includes 3/4" I.P.S. angle stop with back-flow protection, vandal-resistant cap, sweat solder kit, cover tube and wall flange.

Outlet includes 3/4" vacuum breaker, spud coupling and flange.

## PRODUCT FEATURES:

- Exclusive Pressure Compensation feature eliminates the need for the installer to adjust the stop valves, saving time and money and ensuring water savings
- Electronic flush valve with Selectronic™ proximity system for "Hands Free" operation
- Includes UL approved hard-wired AC transformer
- Input Voltage: 100 - 250 VAC, 50 / 60 Hz. Output Voltage: 6 VDC.
- Self-Cleaning Piston operation with integral wiper spring prevents clogging and reduces maintenance
- Piston operation delivers superior flush accuracy and repeatability
- Adjustable tailpiece
- Chemical resistant EPDM seals are unaffected by chloramines and ammonia
- Valve remains closed and does not need to be reset after loss of power or water pressure
- Stadium Feature: Valve automatically switches to water conservation mode during periods of heavy usage
- Fully Mechanical Manual Override Button can flush toilet during a power outage
- Vandal-resistant metal cover plate (for 2-gang electric box supplied by others) with no visible fasteners
- Sensor & electronic controls are fully enclosed and water resistant
- Range can be adjusted manually or by remote control
- Sanitary Flush - Valve automatically flushes after 24 hours of non-use to clean fixture & maintain trap seal
- No external volume adjustment
- 5 second Arming Delay prevents unintentional flushing
- 3-second Flush Delay
- Can be installed left or right-handed

## MODEL NUMBER:

### 6062.101.002 HARD-WIRED AC POWERED:

Includes UL-approved Hard-Wired AC transformer (electrical box by others). 11-1/2" rough-in

### 6061.101.002 MULTI-AC POWERED:

Includes 10' extension cable. One transformer (sold separately) can operate up to 15 faucets and/or flush valves. 11-1/2" rough-in

## OPERATING PRESSURE:


20 psi (flowing)-80 psi (static)

## FLOW REQUIREMENT:

10 gpm (37.9 L/min.)

## ACCESSORIES:

- Cast wall flange (3/4")



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES

## RECOMMENDED SPECIFICATION:


Electronic proximity infrared sensor activated toilet flush valve shall feature self-cleaning piston valve. Includes a UL listed hard-wired power supply that provides 6 VDC power to run system. Includes a fully mechanical manual over-ride that can provide a complete flush without power. Includes cast brass valve body and metal cover with chrome finish and vandal resistant stop cap. Angle stop with back-flow protection and vacuum breaker included. 1.0 gpf / 3.8 Lpf. Flush valve shall be American Standard Model # 606\_101.002

# SELECTRONIC™ EXPOSED 1.0 GPF URINAL FLUSH VALVE HARD-WIRED AC POWERED, SENSOR OPERATED

## LISTINGS:

- ASSE 1037
- ANSI/ASME A112.19.2
- ADA Compliant

## Roughing-in Dimensions



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES  
AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND  
USABLE BUILDING FACILITIES-CHECK LOCAL CODES

PART OF **LIXIL**