




6530.175 Shown



MODEL NUMBER:*

- ❑ **6530.175 Widespread Lavatory**
0.5 gpm Pressure Compensating Vandal-Resistant Multi-Laminar Spray. Rigid gooseneck spout. Vandal-Resistant Wrist Blade Handles. Less drain and pop-up hole.
- ❑ **6532.175 Widespread Lavatory**
0.5 gpm Pressure Compensating Vandal-Resistant Multi-Laminar Spray. Rigid gooseneck spout. Vandal-Resistant Wrist Blade Handles. Grid strainer drain.
- ❑ **6530.145 Widespread Lavatory**
0.5 gpm Pressure Compensating Vandal-Resistant Multi-Laminar Spray. Rigid gooseneck spout. Vandal-Resistant Lever Handles. Less drain and pop-up hole.
- ❑ **6532.145 Widespread Lavatory**
0.5 gpm Pressure Compensating Vandal-Resistant Multi-Laminar Spray. Rigid gooseneck spout. Vandal-Resistant Lever Handles. Grid strainer drain.

GENERAL DESCRIPTION:

Durable cast brass construction. Cast brass valve bodies with 8" rigid copper connection with compression fittings. 1/2" male threaded inlet shanks with brass coupling nuts. 1/4 turn ceramic disc valve cartridges. Choice of Vandal-Resistant Lever or Wrist Blade handles with blue & red color indexes. All brass drain body with 1 1/4" (32mm) tailpiece (on applicable models). 0.5 gpm/1.9L/min. maximum flow rate.

PRODUCT FEATURES:

Pressure Compensating Multi-Laminar Spray:

Provides a constant water flow of 0.5 gpm throughout the pressure range. No mix of air and water.

Solid Brass Construction: Durable - Excellent in high use applications. Ideal for prolonged contact with water.

Ceramic Disc Valve Cartridges: Assures a lifetime of drip-free performance.

Lead Free: Faucet contains $\leq 0.25\%$ total lead content by weighted average.

SUGGESTED SPECIFICATION:

Two handle widespread lavatory faucet shall feature cast brass valve bodies with 8" rigid copper connection. Shall feature water-conserving vandal-resistant 0.5 gpm/1.9L/min. pressure compensating multi-laminar spray. Vandal-Resistant handles. Shall also feature 1/4 turn washerless ceramic disc valve cartridges. Fitting shall be American Standard Model # 653_.1_.5.002.



MONTERREY™ 0.5 GPM


TWO-HANDLE 8" WIDESPREAD LAVATORY FAUCET

WITH RIGID GOOSENECK SPOUT

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ANSI A117.1
ASME A112.18.1
CSA B 125
NSF 372



Product Number	Description	Finish
		Polished Chrome
		002
6530.175	Widespread Lavatory with rigid gooseneck spout. 0.5 gpm/1.9L/min pressure compensating vandal-resistant multi-laminar spray. Vandal-Resistant Wrist Blade Handles. Less drain and pop-up hole.	
6532.175	Widespread Lavatory with rigid gooseneck spout. 0.5 gpm/1.9L/min pressure compensating vandal-resistant multi-laminar spray. Vandal-Resistant Wrist Blade Handles. Grid strainer drain.	
6530.145	Widespread Lavatory with rigid gooseneck spout. 0.5 gpm/1.9L/min pressure compensating vandal-resistant multi-laminar spray. Vandal-Resistant Lever Handles. Less drain and pop-up hole.	
6532.145	Widespread Lavatory with rigid gooseneck spout. 0.5 gpm/1.9L/min pressure compensating vandal-resistant multi-laminar spray. Vandal-Resistant Lever Handles. Grid strainer drain.	



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES
AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND
USABLE BUILDING FACILITIES-CHECK LOCAL CODES