


PRESSURE BALANCE BATH/SHOWER FITTING



T064.502 Bath/Shower Trim Shown

GENERAL DESCRIPTION:

TRIM KIT

3 Function Modern Showerhead at 2.5gpm/9.5L/min. max. flow rate. Metal slip-on diverter spout. Available with metal lever handle. Metal wall escutcheon.

ROUGH VALVE BODY

Cast brass body, washerless ceramic disc valve cartridge with back to back capability, and hot limit safety stop. Cycles from "off" to "cold" to "hot." Pressure balancing cartridge maintains constant output temperature in response to changes in relative hot and cold supply pressure. 1/2" inlets and outlets (choice of direct sweat, threaded, or PEX). Available with screwdriver stops. Rough-in plaster guard designed for use as thin-wall mounting adaptor.



MODEL NUMBER:

TRIM KITS:

- T064.502 Serin BATH/SHOWER Trim Kit Metal Lever Handle. L ESS Valve Body.
- ☐ T064.501 Serin SHOWER ONLY Trim Kit Metal Lever Handle. LESS Valve Body.
- T064.500 Serin VALVE ONLY Trim Kit Metal Lever Handle. L ESS Valve Body.

ROUGH VALVES:

- R110 Pressure Balance Rough Valve Body only Direct sweat inlets/outlets. LESS trim.
- R110SS Pressure Balance Rough Valve Body only with Screwdriver stops
 - Direct sweat inlets/outlets. Screwdriver stops. LESS trim.
- R115 Pressure Balance Rough Valve Body only Female thread inlets/outlets. LESS trim.
- R115SS Pressure Balance Rough Valve Body only with Screwdriver stops
 Female thread inlets/outlets. Screwdriver stops. LESS trim.
- R117 Pressure Balance Rough Valve Body only PEX inlets/Direct sweat outlets. LESS trim.
- R117SS Pressure Balance Rough Valve Body only with Screwdriver stops
 PEX inlets/Direct sweat outlets. Screwdriver stops. LESS trim.

PRODUCT FEATURES:

3-Function Showerhead: User can personalize shower experience to their needs.

Rough Valve Body: Durable quality that will last a lifetime. Ideal material for prolonged contact with water.

Ceramic Disc Valve Cartridge: Assures a lifetime of drip-free performance. Allows easy control over both water temperature and volume.

Pressure Balancing Valve Cartridge: Maintains constant output temperature in response to changes in relative hot and cold supply pressure. Diaphragm system engineered to eliminate cross flow. Avoids failure due to mineral deposits - ideal for use in hard water.

Back-to-Back Capability: Hot and cold can be reversed quickly and easily.

Adjustable Hot Limit Safety Stop: Limits the amount of hot water allowed to mix with cold. Reduces the risk of accidental scalding.

Exclusive Plaster Guard: Plaster guard is designed to protect valve during installation and serve as a mounting plate for thin-wall installations. Two piece design allows valve to be tested prior to trim installation.


Wide Rough-in Range: From 1-5/8" to 3-1/4".


SUGGESTED SPECIFICATION:

Bath/shower fitting shall feature 3 function showerhead with Max. 2.5gpm/9.5L/min. flow rate. Shall feature a cast brass valve body. Shall feature ceramic disc valve cartridge which is capable of back-to-back installation. Fitting shall be equipped with pressure balancing cartridge engineered to eliminate cross flow and avoid failure due to mineral deposits. Shall also feature hot limit safety stop. Fitting shall be: Rough Valve Body - American Standard Model # R11_____, Trim Kit - American Standard Model # T064.50_.____.



PRESSURE BALANCE BATH/SHOWER FITTING





CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ANSI A 117.1 ASSE 1016 ASME A112.18.1 CSA B125.1

Meets the American Disabilities
Act Guidelines and ANSI A117.1
Requirements for the physically challenged.

				Finish O	ptions
TS *	Product			Polished Chrome	Sann
¥	Number	Description		002	295
M	T064.502	Bath/Shower Trim Kit. Metal Lever Handle. FloWise Showerhead. LESS Valve Body.	Ė		
Ħ	T064.501	Shower Only Trim Kit. Metal Lever Handle. FloWise Showerhead. LESS Valve Body.	Ė		
	T064.500	Valve Trim Only . Metal Lever Handle. LESS Valve Body.	Ė		

SES	Product Number	Description
300	R110	Rough Valve Body less trim. Direct Sweat inlets/outlets.
Æ	R110SS	Rough Valve Body less trim. Direct Sweat inlets/outlets with Screwdriver Stops.
/AL	R115	Rough Valve Body less trim. Female Thread inlets/outlets.
Ĭ.	R115SS	Rough Valve Body less trim. Female Thread inlets/outlets with Screwdriver Stops.
oug	R117	Rough Valve Body less trim. PEX inlets/ Direct Sweat outlets.
E S	R117SS	Rough Valve Body less trim. PEX inlets/ Direct Sweat outlets with Screwdriver Stops.

^{*} TRIM & ROUGH MUST BE ORDERED SEPARATELY.