

CHAMPION® 4 MAX RIGHT HEIGHT® ELONGATED TOILET

BARRIER FREE

VITREOUS CHINA

CHAMPION® 4 MAX RIGHT HEIGHT® ELONGATED TOILET

□ 231AA.104

- Features Champion® Flushing System
- Vitreous china
- High Efficiency Toilet (HET), ultra-low consumption (1.28 gpf/4.8 Lpf), utilizes 20% less water
- Meets EPA WaterSense® Criteria
- PowerWash® rim scrubs bowl with each flush
- Includes color match bowl caps
- EverClean® Surface included
- 4" piston-action Accelerator[™] flush valve
- 2-3/8" trapway
- 16-1/2" rim height for accessible applications
- 12" (305mm) rough-in
- Generous 9" x 8" water surface area
- Chrome finish trip lever is supplied
- 1,000g MaP Score** at 1.28gpf
- 10 year warranty



Nominal Dimensions:

768 x 441 x 791mm (30-1/4" x 17-3/8" x 31-1/8")

Fixture only, seat and supply sold separately

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.2-2008/CSA B45.1-08 for Vitreous China Fixtures
- US EPA WaterSense® Specification for HETs

** Maximum Performance (MaP) testing performed by

IAPMO R&T Lab. MaP Report conducted by Gauley Associates Ltd. and Koeller and Company.


☐ Color: ☐ White ☐ Bone ☐ Linen ☐ Black

solid plastic seat and cover

☐ Seat: #5325.010 Elongated Champion® Slow Close

MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ICC ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES.





NOTES:

THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO C/L OF OUTLET. SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.

* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.









© 2018 AS America Inc.





To Be Specified:

Supply with stop: