

OAK HILL® LAVATORY WALL MOUNT FAUCET -LEVER HANDLES





- Designed with external waterways and traditional two handle and spout configuration
- Can be installed as a wall mount or lavatory mount faucet
- Ceramic disc valve cartridge
- Cast brass spout
- Low flow rate: 1.2 gpm (4.5 L/min)
- Lead Free faucet contains ≤0.25% total lead content by weighted volume

CODES AND STANDARDS

Meets or Exceeds ASME A112.18.1/ CSA B125.1, NSF 61/Section 9

EPA WaterSense® Certified


Certified Compliant with ≤0.25% Weighted Average Lead Content Regulations

CEC and CALGreen® Compliant

AVAILABLE FINISHES	FINISH CODE
Polished Chrome	100
Brushed Nickel	144
Platinum Nickel	150
Satin Brass	427

DESCRIPTION	PRODUCT NUMBER
1.2 gpm (4.5 L/min)	
Wall Mount Faucet	D3515545C.XXX

ROUGH-IN DIAGRAM SHOWN ON NEXT PAGE







OAK HILL® LAVATORY WALL MOUNT FAUCET -LEVER HANDLES

SINK INSTALLATION _6-15/16"_ (176 mm) ___ 8" ___ (203 mm) _ 4-3/16" _ (106 mm) -2-3/16" DIA. (58 mm) 3-1/16"-(78 mm) 14-1/8" (359 mm) __ 6-1/2" __ (165.2 mm) **WALL INSTALLATION** _6-15/16"_ (176 mm) 13/16" MIN. (19.5 mm) 1-1/4" MAX. (32.2 mm) _ 4-3/16"_ (106 mm) HOLE SIZE IN WALL 1-5/16" MIN. (33 mm) 1-1/4" MAX. (45 mm) FINISHED WALL CROSS BRACE — 6-1/2" — (165.2 mm) WALL STUDS 1/2" ELBOW WITH MOUNTING FLANGE

IMPORTANT: These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.