34 271 **CONCETTO**[™]

SINGLE HOLE SINGLE-HANDLE S-SIZE BATHROOM FAUCET 1.2 GPM LESS DRAIN

STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- GROHE EcoJoy[™]
- GROHE QuickFix® installation
- 7 5/16" Faucet height (when in use)
- 3 ¹⁵/₁₆" Spout reach
- 2 %/16" Aerator height
- Solid brass body
- Single lever handle
- 23 1/2'' Nylon braided flex hoses
- CALGreen/CEC compliant
 1 2gpm (WaterSense)
- 1.2gpm (WaterSense)
 Vessel sink pop-up drain (28 754) sold separately
- Grid drain (28 951) sold separately
- Thermal Disinfection up to 82°C (180°F)



Pure Frende

an Wasser

PRODUCT FEATURES:

- GROHE StarLight®
- GROHE SilkMove®
- GROHE EcoJoy™

GROHE QuickFix®

CERTIFICATIONS:



- ADA
- WaterSense
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- · Complies with lead plumbing laws

AVAILABLE FINISHES:

3427100A

GROHE StarLight® Chrome

34271ENA

Brushed Nickel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 08-09-2022

US Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us. Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



34 271 **CONCETTO**™

SINGLE HOLE SINGLE-HANDLE S-SIZE BATHROOM FAUCET 1.2 GPM LESS DRAIN

TECHNICAL DATA:

Product Height	6-1/8 in
Product Length	5-3/4 in
Product Width	1-13/16 in
Fitting Spout Height	2-9/16 in
Fitting Spout Reach	3-15/16 in
Fitting Handle Height	6-1/8 in
GPM (Min)-GPM (Max)	1.2 gal (US)/min
Fitting No of Holes Required	1

 $7_{(15)}^{5}_{16}$ " $6_{1/6}$ " 01^{13}_{16} " 021^{13}_{16} " $020^{\circ} 2^{9}_{16}$ "

Pure Freude an Wasser

