

24 352

**ATRIO®**

SINGLE HOLE SINGLE-HANDLE  
DECK MOUNT VESSEL SINK  
FAUCET 1.2 GPM



GROHE SPA

**STANDARD SPECIFICATION:**

- GROHE SilkMove®
- GROHE StarLight®
- GROHE EcoJoy™
- 16 5/8" Faucet height
- 7 1/16" Swivel spout reach
- 12 13/16" Aerator height
- Nylon braided flex hoses
- CALGreen/CEC compliant
- 1.2gpm (WaterSense)



**PRODUCT FEATURES:**



-  GROHE StarLight®
-  GROHE SilkMove®
-  GROHE EcoJoy™

**CERTIFICATIONS:**



- ADA
- WaterSense
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 372
- NSF 61
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

**AVAILABLE FINISHES:**

- 24352000  GROHE StarLight® Chrome
- 24352ENO  Brushed Nickel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 05-08-2023

**US**  
Tel: 1.630.582.7711 Fax: 1.630.582.7722  
For the most current Specification Sheet,  
go to [www.grohe.us](http://www.grohe.us).

**Canada**  
Tel: 1.888.644.7643 Fax: 1.905.366.2071  
For the most current Specification Sheet,  
go to [www.grohe.ca](http://www.grohe.ca).

**PART OF LIXIL**

24 352

**ATRIO®**

SINGLE HOLE SINGLE-HANDLE  
DECK MOUNT VESSEL SINK  
FAUCET 1.2 GPM



GROHE SPA

**TECHNICAL DATA:**

Product Height	16-5/8 in
Product Length	8-1/16 in
Product Width	5-1/2 in
Fitting Spout Height	12-13/16 in
Fitting Spout Reach	7-1/16 in
GPM (Min)-GPM (Max)	1.2 GPM
Fitting No of Holes Required	1

