

29 177

ALLURE NEW

SINGLE FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM



GROHE SPA

STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE TurboStat® compact cartridge with wax thermostatic element
- GROHE QuickFix® (concealed mounting screws)
- Thermostatic temperature control with GROHE SafeStop safety button at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- Volume control with ceramic disc stop valve, 120°
- Metal trim angle adjustable up to 6°
- Volume control with ceramic disc stop valve, 120°
- Requires Rapido® Smartbox Rough-in Valve (35 601) (sold separately)







PRODUCT FEATURES:

-  GROHE StarLight®
-  GROHE TurboStat®
-  GROHE QuickFix®
-  GROHE SafeStopPlus

CERTIFICATIONS:

- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.1016

AVAILABLE FINISHES:

- 29177001  GROHE StarLight® Chrome
- 291772431  Matte Black
- 29177EN1  Brushed Nickel InfinityFinish™
- 29177GN1  Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 04-26-2023

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF **LIXIL**

29 177

ALLURE NEW

SINGLE FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM



GROHE SPA

TECHNICAL DATA:

Product Height	2-3/4 in
Product Width	1-11/16 in

