23 824

LINEARE™

Pure Frende an Wasser

SINGLE HOLE SINGLE-HANDLE XS-SIZE **BATHROOM FAUCET 1.2 GPM**

STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- GROHE EcoJoy™
- GROHE QuickFix® Plus installation
- GROHE AquaGuide adjustable aerator 20°-40°
- 7 3/8" Faucet height (open position)
- 6 1/8" Faucet height (closed position)
- 4 3/16" Spout reach
- 3 3/4" Aerator height
- · Solid brass construction with metal lever
- 23 1/2" Nylon brained flex hoses
- CALGreen/CEC compliant
- 1.2gpm (WaterSense)



PRODUCT FEATURES:

- **GROHE StarLight®**
 - **GROHE SilkMove®**
- - **GROHE EcoJoy™**
- - **GROHE QuickFix®**

CERTIFICATIONS:







- ASMF A112.18.1



- ADA
- WaterSense
- · CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Energy Policy Act of 1992
- NSF 61
- NSF 372
- CSA B125.1
- · Complies with lead plumbing laws

AVAILABLE FINISHES:

2382400A

GROHE StarLight® Chrome

23824243A

Matte Black

23824A0A

Hard Graphite

23824ENA

Brushed Nickel InfinityFinish™

23824GNA

Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations. We reserve the right to make revisions without notice to product specifications. 04-04-2023

US Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us.

Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



23 824

LINEARETM



SINGLE HOLE SINGLE-HANDLE XS-SIZE BATHROOM FAUCET 1.2 GPM

TECHNICAL DATA:

Product Height 6-1/8 in

Product Length 6 in

Product Width 1-3/4 in

Fitting Spout Height 3-3/4 in

Fitting Spout Reach 4-3/16 in

Fitting Handle Height 6-1/8 in

GPM (Min)-GPM (Max) 1.2 gal (US)/min

Fitting No of Holes Required 1

