29 298 **DEFINED**[™] PRESSURE BALANCE VALVE TRIM

Pure Freude an Wasser



STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE SilkMove®
- Metal handle
- Metal trim plate with GROHE QuickFix®
- Includes pressure balance cartridge with double ceramic technology
- 5.2gpm (bottom) and 3.0gpm (top port) at 45 psi (19 L/min)
- Requires GrohSafe 3.0 Rough-in Valve (35 110, 35 111, 35 112, 35 113, 35 114, 35 115, or 35 116) (sold separately)



PRODUCT FEATURES:

GROHE StarLight®

GROHE SilkMove®

GROHE QuickFix®

CERTIFICATIONS:



- ADA
- CSA B125.1
- ASME A112.18.1

AVAILABLE FINISHES:

29298000 Gf **292982430** M

29298EN0

GROHE StarLight® Chrome

Matte Black

Brushed Nickel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 04-05-2023

US Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us. Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



29 298 **DEFINED**[™] PRESSURE BALANCE VALVE TRIM

Pure Freude an Wasser



TECHNICAL DATA:

Product Height 7.421 in

Product Length 2.444 in

Product Width 7-27/64 in

Fitting Handle Height 2-7/16 in

