23 671 **EUROCUBE**[®] SINGLE HOLE SINGLE-HANDLE DECK

MOUNT VESSEL SINK FAUCET 1.2 GPM

STANDARD SPECIFICATION:

- GROHE SilkMove[®]
- GROHE StarLight[®]
- GROHE EcoJoy™
- GROHE QuickFix[®] installation
- 13 ⁷/₁₆" Faucet height
- 7 1/16" Spout reach
- 9 ¹³/₁₆" Aerator height
- Solid brass body
- Single loop handle
- 15 ³/₁₆" Nylon braided flex hoses
- CALGreen/CEC compliant
- 1.2gpm (WaterSense)
- Vessel sink pop-up drain (48 657) sold separately
- Vessel sink pop-up drain (48 656) sold separately
- Grid drain (28 951) sold separately

PRODUCT FEATURES:

GROHE StarLight®

GROHE SilkMove®

GROHE EcoJoy[™]

GROHE QuickFix®





- ADA
- WaterSense
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- NSF 372
- CSA B125.1
- ASME A112.18.1
- · Complies with lead plumbing laws

AVAILABLE FINISHES:



NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 04-04-2023

US Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us. Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



Pure Freude an Wasser





23 671 **EUROCUBE®** SINGLE HOLE SINGLE-HANDLE DECK MOUNT VESSEL SINK FAUCET 1.2 GPM

Pure Freude an Wasser



TECHNICAL DATA:

Product Height	340 mm
Product Length	225 mm
Product Width	55 mm
Fitting Spout Height	250 mm
Fitting Spout Reach	180 mm
Fitting Handle Height	312 mm
GPM (Min)-GPM (Max)	1.2 gal (US)/min
Fitting No of Holes Required	1

