14 469

EUROCUBE®



PRESSURE BALANCE VALVE TRIM WITH CARTRIDGE

STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE SilkMove®
- Metal handle
- Metal trim plate with GROHE QuickFix®
- Includes pressure balance cartridge with double ceramic technology
- 5.2gpm (bottom) and 3.0gpm (top port) at 45psi (19 L/min)
- Requires GrohSafe™ 3.0 Rough-in Valve (35 110), (35 111), (35 112), (35 113), (35 114), (35 115), or (35 116) (sold separately)



PRODUCT FEATURES:



ROHE SilkMove®

GROHE QuickFix®

CERTIFICATIONS:



- ADA
- CSA B125.1
- ASME A112.18.1

AVAILABLE FINISHES:

 14469000
 GROHE StarLight® Chrome

 144692430
 Matte Black

 14469A00
 Hard Graphite

 14469EN0
 Brushed Nickel InfinityFinish™

 14469GN0
 Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations. We reserve the right to make revisions without notice to product specifications. 04-04-2023



EUROCUBE®



PRESSURE BALANCE VALVE TRIM WITH CARTRIDGE

TECHNICAL DATA:

Product Height 167 mm

Product Length 57 mm

Product Width 159 mm

