

31 518

## CONCETTO™

SINGLE-HANDLE BAR FAUCET 1.5 GPM

Pure Freude  
an Wasser



### STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- 11 7/8" Faucet height
- 8 1/16" Aerator height
- 6" Faucet reach
- 360° Swivel radius
- Solid brass body
- Nylon braided flex hoses
- Optional pivot 90° or 360°
- Guide installation system
- Adjustable flow rate limiter
- 1.5gpm



### PRODUCT FEATURES:





-  GROHE StarLight®
-  GROHE SilkMove®
-  Speed Clean®

### CERTIFICATIONS:



- ADA
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Energy Policy Act of 1992
- NSF 61
- NSF 372
- Complies with lead plumbing laws

### AVAILABLE FINISHES:

- 31518000**  GROHE StarLight® Chrome
- 315182430**  Matte Black
- 31518DC0**  SuperSteel InfinityFinish™
- 31518GN0**  Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 04-05-2023

**US**  
Tel: 1.630.582.7711 Fax: 1.630.582.7722  
For the most current Specification Sheet,  
go to [www.grohe.us](http://www.grohe.us).

**Canada**  
Tel: 1.888.644.7643 Fax: 1.905.366.2071  
For the most current Specification Sheet,  
go to [www.grohe.ca](http://www.grohe.ca).

PART OF **LIXIL**

31 518

**CONCETTO™**

SINGLE-HANDLE BAR FAUCET 1.5 GPM

Pure Freude  
an Wasser



**TECHNICAL DATA:**

Product Height	301 mm
Product Length	190 mm
Product Width	142 mm
Fitting Spout Height	205 mm
Fitting Spout Reach	153 mm
Fitting Handle Height	55 mm
GPM (Min)-GPM (Max)	1.5 gal (US)/min
Fitting No of Holes Required	1

