30 378 **DEFINED**[™] SINGLE-HANDLE PULL DOWN DUAL

SPRAY BAR FAUCET 1.75 GPM

STANDARD SPECIFICATION:

- GROHE SilkMove[®]
- GROHE StarLight®
- Pull-down dual spray with toggle function: switches between regular water flow and spray without turning off the water
- 14 5/8" Faucet height
- 8 7/16" Aerator height
- 7 5/16" Faucet reach
- SpeedClean® anti-lime system
- Forward rotation lever does not hit backsplash
- 360° Swivel radius
- Solid brass body
- Flexible connection hoses
- 1.75gpm flow rate
- CALGreen compliant



Pure Freude

an Wasser

PRODUCT FEATURES:

GROHE SilkMove®

GROHE StarLight®

Speed Clean[®]

CERTIFICATIONS:



- ADA
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 372
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

AVAILABLE FINISHES:

30378000 GROHE StarLight® Chrome

303782430

30378DC0

Matte Black

SuperSteel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 04-05-2023

US Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us. Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



30 378 **DEFINED**[™] SINGLE-HANDLE PULL DOWN DUAL SPRAY BAR FAUCET 1.75 GPM

Pure Freude an Wasser



TECHNICAL DATA:

Product Height	14-5/8 in
Product Width	5-1/16 in
Fitting Spout Height	8-7/16 in
Fitting Spout Reach	7-5/16 in
GPM (Min)-GPM (Max)	1.75 gal (US)/min

