




SELECTRONIC™ FloWise® EXPOSED 1.28/1.1 GPF DUAL FLUSH TOILET FLUSH VALVE HARD-WIRED AC POWERED, SENSOR OPERATED



GENERAL DESCRIPTION:

Exposed, Hard-wired AC Powered, Sensor Operated Selectronic™ Water Closet Flush Valve for floor-mounted or wall-hung 1-1/2" top spud bowls.

Inlet includes 1" I.P.S. angle stop with back-flow protection, vandal-resistant cap, sweat solder kit, cover tube and wall flange.

Outlet includes 1-1/2" vacuum breaker, spud coupling and flange.

PRODUCT FEATURES:

- Light flush (1.1 gpf: 30% water savings) if user is in detection zone for 60 seconds or less
- Standard flush (1.28 gpf 20% water savings) if user is in detection zone for more than 60 seconds
- Electronic flush valve with Selectronic™ proximity system for "Hands Free" operation
- Includes UL approved hard-wired AC transformer
- Input Voltage: 100 - 250 VAC, 50 / 60 Hz. Output Voltage: 6 VDC.
- Self-Cleaning Piston operation with integral wiper spring prevents clogging and reduces maintenance
- Piston operation delivers superior flush accuracy and repeatability
- Adjustable tailpiece
- Chemical resistant EPDM seals are unaffected by chloramines and ammonia
- Valve remains closed and does not need to be reset after loss of power or water pressure
- Fully Mechanical Manual Override Button can flush toilet during a power outage
- Vandal-resistant metal cover plate (for 2-gang electric box supplied by others) with no visible fasteners
- Sensor & electronic controls are fully enclosed and water resistant
- Range can be adjusted manually or by remote control
- Sanitary Flush - Valve automatically flushes after 24 hours of non-use to clean fixture & maintain trap seal
- No external volume adjustment
- 5 second Arming Delay prevents unintentional flushing
- 3-second Flush Delay
- Can be installed left or right-handed

MODEL NUMBER:

6067.721.002 HARD-WIRED AC POWERED:
Includes UL-approved Hard-Wired AC transformer (electrical box by others). 11-1/2" rough-in

6068.721.002 MULTI-AC POWERED:

Includes 10' extension cable. One transformer (sold separately) can operate up to 15 faucets and/or flush valves. 11-1/2" rough-in

OPERATING PRESSURE:


25 psi (flowing)-80 psi (static)

FLOW REQUIREMENT:

25 gpm (94.6 L/min.)

ACCESSORIES:

- Cast wall flanges (1" & 1-1/2")
- Solid ring pipe supports (2-1/2" & 6" C-E)
- Split ring pipe supports (2-1/2" & 6" C-E)



 MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES

RECOMMENDED SPECIFICATION:

Electronic proximity infrared sensor activated toilet flush valve shall feature self-cleaning piston valve. Includes a UL listed hard-wired power supply that provides 6 VDC power to run system. Flush volume is determined by amount of time user is in detection zone. 60 seconds or less: 1.1 gpf/4.2 Lpf. More than 60 seconds: 1.28 gpf/4.9 Lpf. Includes a fully mechanical manual over-ride that can provide a complete flush without power. Includes cast brass valve body and metal cover with chrome finish and vandal resistant stop cap. Angle stop with back-flow protection and vacuum breaker included. Flush valve shall be American Standard Model # 606_.721.002.

SELECTRONIC™ FloWise® EXPOSED
1.28/1.1 GPF DUAL FLUSH TOILET FLUSH VALVE
HARD-WIRED AC POWERED, SENSOR OPERATED

LISTINGS:

- ASSE 1037
- ANSI/ASME A112.19.2
- ADA Compliant

Roughing-in Dimensions

