

**TOWNSEND® 64" x 38" (60" x 34" Clear)  
 ADA SOLID SURFACE SHOWER BASE**

- 6438AM-FCOL** Barrier Free Front Center Drain with Trench Cover



**Product Features:**

- Durable 100% solid, non-porous material
- Smooth matte surface
- Integral 3-sided 1" tiling / water retention flange for easy installation
- Repairable and renewable surface
- Fungi and bacterial resistant
- Self-extinguishing
- UV resistant
- Resistant to stains and impact
- Easy maintenance and cleaning
- Barrier Free compliant when installed according to Barrier Free guidelines
- Drain not included

SEE REVERSE SIDE FOR ROUGHING-IN DIMENSIONS

**Nominal Dimensions:**

64" x 38" x 1-3/8"  
 (1626 x 965 x 34mm)

**Shower Base Includes:**

- Removable Brushed Stainless Steel trench drain cover

**Compliance Certifications -**


**Meets or Exceeds the Following Specifications:**

- CSA B45.5 / IAPMO Z124
  - IAPMO R&T cUPC
  - ICC A117.1
  - Class A rating per ASTM E84 tunnel test
- |              |              |              |
|--------------|--------------|--------------|
|              | <u>Flame</u> | <u>Smoke</u> |
| ASTM E84-17a | 0 (Zero)     | 20           |
- Tested against CAN/ULC S102.2-10
- |                   |              |              |
|-------------------|--------------|--------------|
|                   | <u>Flame</u> | <u>Smoke</u> |
| CAN/ULC S102.2-10 | 0 (Zero)     | 15           |

**To Be Specified - Required**

- Colour: (speciy American Standard fixture color)

**6438AM-FCOL**  
**Barrier Free Front Center Drain**  
**with Trench Cover**



<b>GENERAL SPECIFICATIONS FOR 6438AM SHOWER BASE</b>	
INSTALLED SIZE	1626mm x 965mm (64 x 38 In.)
WEIGHT	62.8 Kg. (138 Lbs.)
SHOWER WELL AT SUMP	1562mm x 902mm (61-1/2 x 35-1/2 In.)
SHOWER WELL AT RIM	1586mm x 914mm (62-3/8 x 36 In.)
FLOOR LOADING (PROJECTED AREA)	40 Kgs/Sq. m. (8 Lbs./Sq. Ft.)