

CHAMPION® 4 CHAIR HEIGHT ROUND FRONT COMPLETE TOILET

BARRIER FREE

VITREOUS CHINA

CHAMPION® 4 CHAIR HEIGHT ROUND FRONT COMPLETE TOILET

□ 731BA.101S.020

- Clog resistant Can flush 2.2 pounds of solid waste in a single flush
- Superior solid waste removal with 1,000 gram MaP score**
- 4" piston action Accelerator™ flush valve
- Vitreous china
- 2-3/8" fully-glazed trapway
- Toilet stays cleaner longer with EverClean® surface.
 EverClean surface inhibits the growth of stainand odor-causing bacteria, mold, and mildew on the surface
- Meets definition for HET (High Efficiency Toilet)
- High efficiency (1.28 gpf/4.8 Lpf)
- Meets EPA WaterSense® Criteria
- ADA compliant for ADA accessible applications
- Chrome finish handle
- Sweeping pier on bowl helps omit buildup of dust and dirt in the crevice between the tank and the bowl
- 100% factory flush tested
- Includes Slow Close Seat
- Lifetime warranty on chinaware, 10 year warranty on all mechanical parts and 1 year warranty on seat
- Easy Installation. Everything needed for toilet installation is included and can be hand tightened
- Complete Toilet includes: Wax ring, 2 bolt caps, closet bolts, seat and handle

Nominal Dimensions:

28-1/4" x 17-7/8" x 31-3/16" (717 x 454 x 792mm)

Compliance Certifications - Meets or Exceeds the Following Specifications:

 ASME A112.19.2/CSA B45.1 for Vitreous China Fixtures




^{**} Maximum Performance (MaP) testing performed by IAPMO R&T Lab. MaP Report conducted by Gauley Associates Ltd. and Koeller and Company.



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ICC ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES.





NOTES:

THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO C/L OF OUTLET. SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.

* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME A112.19.2/CSA B45.1 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.







© 2023 AS America Inc.