

# Titan® Chair Height Elongated Complete Toilet w/Aquaguard® Insulated Tank VITREOUS CHINA WITH EVERCLEAN®

**BARRIER FREE** 

# Titan® Chair Height Elongated Complete Toilet With Aquaguard® Insulated Tank

### ☐ 733AA.051

- Includes Aquaguard® liner which helps omit tank condensation
- · Industry-leading clog resistance with a 4" non-adjustable, piston action Accelerator™ flush valve and a 2-3/8" fully-glazed trapway
- Includes EverClean® surface which inhibits the growth of stain and odor causing bacteria, mold, and mildew on the surface
- Vitreous china
- Low consumption 1.6 gallons per flush (6.0 Lpf)
- · Easy installation Everything needed for toilet installation is included and can be hand tightened
- 12" (305mm) rough-in
- 16-1/2" rim height for accessible applications
- Elongated siphon action jetted bowl
- Speed Connect® tank/bowl coupling system
- Chrome-plated handle
- Sweeping pier on bowl which helps omit buildup of dust and dirt between the tank and the bowl
- 100% factory flush tested
- 2 bolt caps
- Includes a plastic, color-matched, slow-close toilet seat
- Wax ring gasket with closet bolts
- · Lifetime warranty on chinaware, 10 year warranty on all mechanical parts, and 1 year warranty on seat

### **Nominal Dimensions:**

30-1/4" x 18" x 31-3/16" (768 x 457 x 792mm)

## **Compliance Certifications -**Meets or Exceeds the Following **Specifications:**


 ASME A112.19.2/CSA B45.1 for Vitreous China Fixtures

## To Be Specified:

- □ Color: □ White □ Linen □ Bone
- Supply with stop:

MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ICC ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES.





THIS COMBINATION IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO C/L OF

\*\*DIMENSIONS SHOWN FOR LOCATION OF SUPPLY ARE SUGGESTED.SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

