
American Standard

Townsend® Water-Saving Pressure Balance Bath/Shower Trim with Double Ceramic Pressure Balance Cartridge



MODEL NUMBER:

TRIM KITS:

- TU353508 Townsend Bath/Shower Trim Kit with Pressure Balance Cartridge Lever handle. Water-saving showerhead. LESS valve body.
- TU353507 Townsend Shower ONLY Trim Kit with Pressure Balance Cartridge Lever handle. Water-saving showerhead. LESS valve body.
- TU353500 Townsend Valve Only Trim Kit with Double Ceramic Pressure Balance Cartridge Lever handle. LESS valve body.

For use with Flash[™] Rough Valve Bodies

TU353508 Bath/Shower Trim Shown

GENERAL DESCRIPTION:

Double Ceramic Pressure Balance Cartridge: Features one-piece design with ceramic discs and ceramic balancing spool. Includes integrated check valves and hot limit safety stop. Cartridge capable of back to back capability. Ceramic balancing spool maintains constant output temperature in response to changes in relative hot and cold supply pressure. Washerless ceramic discs provide smooth handle movement and are unaffected by harsh water conditions.

Trim: Features 6" water-saving showerhead with a maximum 1.75 gpm/6.6 L/min. flow rate. Metal slip-on diverter spout. Metal wall valve trim with metal lever.

PRODUCT FEATURES

One-Piece Cartridge: Simplifies installation and maintenance.

Double Ceramic Pressure Balance Cartridge: Combination of Ceramic Disc Mixing Valve and a Ceramic Balancing Spool in a one-piece cartridge.

Ceramic Disc Mixing Valve: Assures a lifetime of drip-free performance and smooth handle operation.

Ceramic Balancing Spool: Maintains a constant output temperature in response to changes in relative hot and cold supply pressure. Ceramic material is unaffected by mineral deposits and harsh water conditions.

Integrated Check Valves: Engineered to eliminate cross flow.

Adjustable Hot Limit Safety Stop: Limits the amount of hot water allowed to mix with cold. Reduces the risk of accidental scalding.


Comfort Zone: Offers a wider shower range to fine tune the desired temperature within the useful temperature zone.

Back-to-Back Capability: Hot and cold can be reversed quickly and easily.

Water Saving: Saves 30% water usage.

SUGGESTED SPECIFICATION

Bath/shower fitting shall feature water saving showerhead with Max. 1.75 gpm/6.6 L/min. flow rate. Shall feature double ceramic pressure balance cartridge. Cartridge is capable of back to back installation and shall feature integrated check valves to eliminate cross flow. Capable of meeting ASSE1016 @1.3gpm. Cartridge shall also feature hot limit safety stop. Fitting shall be: American Standard - Trim Kit Model # TU35350.___ and Flash Valve Body Model # RU10___.



American Standard


Townsend[®] Water-Saving Pressure Balance Bath/Shower Trim with Double Ceramic Pressure Balance Cartridge

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ASSE 1016 / ASME A112.18.1016 / CSA B125.16 ASME A112.18.1 / CSA B125.1 Rated to meet ASSE 1016 @ 1.3gpm

CEC



			Finish Options					
	Product		Polished Chrome	Brushed Nickel	Legacy Bronze	Matte Black	Brushed Cool Sunrise	Polished Nickel
	Number	Description	002	295	278	243	GN0	013
	TU353508	Bath/Shower Trim Kit. Metal lever handle. Water-saving showerhead. Includes cartridge. LESS valve body.	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
	TU353507	Shower Only Trim Kit. Metal lever handle. Water-saving showerhead. Includes cartridge. LESS valve body.	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
	TU353500	Townsend Valve Only Trim Kit with Double Ceramic Pressure Balance Cartridge Lever handle. LESS valve body.	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark

* TRIM & ROUGH MUST BE ORDERED SEPARATELY.

DIES	Product Description	Without Screwdriver Stops	With Screwdriver Stops
^{-lash™} ROUGH VALVE BO	Rough Valve Body. Universal* inlets/outlets.	RU101	RU101SS
	Rough Valve Body. Stub-out inlets/outlets for Press-Fit Fittings.	RU102	RU102SS
	Rough Valve Body. PEX inlets/Universal outlets for Crimp Ring PEX system (ASTM F1807).	RU107	RU107SS
	Rough Valve Body. PEX Elbow inlets/Universal outlets for Crimp Ring PEX system (ASTM F1807).	RU107E	RU107ESS
	Rough Valve Body. PEX inlets/Universal outlets for Cold Expansion PEX system (ASTM F1960).	RU108	RU108SS
	Rough Valve Body. PEX Elbow inlets/Universal outlets for Cold Expansion PEX system (ASTM F1960).	RU108E	RU108ESS
	Rough Valve Body. CPVC inlets/Universal outlets.	RU109	RU109SS

	Product Number	Product Description
ACG	M970649-YYY0A	Deep Rough-In Kit

ÁDÀ

Meets the American Disabilities Act Guidelines and **ANSI A117.1** Requirements for the physically challenged.