

### DECORUM™ FloWise® 0.5 GPF HIGH EFFICIENCY URINAL

- Sleek, modern, compact design
- Vitreous china
- High Efficiency (1.9 Lpf/0.5 gpf)
- Permanent EverClean® surface inhibits the growth of stain- and odor-causing bacteria, mold, and mildew on the surface
- Powerful washdown action
- 3/4" inlet spud
- Outlet connection threaded 2" inside (NPTF)
- Wall hanger
- Fixture only
- ADA compliant
- Meets ANSI flush requirements at 0.5 GPF

**6042.005** Top spud

**6043.005** Back spud

#### Nominal Dimensions:

338 x 356 x 459mm  
(13-1/4" x 14" x 18")

Recommended working pressure – between  
20 psi at valve when flushing and 80 psi static

#### Compliance Certifications -

##### Meets or Exceeds the Following Specifications:

- ASME A112.19.2-2008/CSA B45.1-08 for Vitreous China Fixtures

#### To Be Specified:

Color:  White

Flush Valve:

0.5 gpf Sensor-Operated:

- American Standard Selectronic®  
#6063.051.002 DC Powered (Top Spud)
- American Standard Selectronic®  
#6062.305.002 AC Powered (Back Spud)

0.5 gpf Manual:

- American Standard #6045.051.002 (Top Spud)



SEE REVERSE FOR ROUGHING-IN DIMENSIONS

EVERCLEAN®  
Surface



