23 085

BAULOOP®

Pure Freude an Wasser GROHE

SINGLE HOLE SINGLE-HANDLE S-SIZE BATHROOM FAUCET 1.2 GPM LESS DRAIN

STANDARD SPECIFICATION:

- GROHE LongLife
- GROHE StarLight®
- GROHE Zero isolated inner waterways lead and nickel free
- GROHE EcoJoy[®]
- 6 15/16" Faucet height (open position)
- $5 \frac{13}{16}$ " Faucet height (closed position)
- 3 3/4" Spout reach
- 3 3/8" Aerator height
- · Quick installation system
- Nylon braided flex hoses
- CALGreen/CEC compliant
- 1.2gpm (4.56 L/min)
- Sold Separately: sink pop-up drain with overflow (48656) or sink pop-up drain without overflow (48657)
- Grid drain (28 951) sold separately
- This faucet will accept Low Flow Kits (sold separately): 48186000 (1.0gpm - WaterSense Certified), 48187000 (0.5gpm), 48188000 (0.35gpm)



PRODUCT FEATURES:



GROHE StarLight®



GROHE EcoJoy™

CERTIFICATIONS:







- ADA
- WaterSense
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61NSF 372
- CSA B125.1
- ASME A112.18.1
- · Complies with lead plumbing laws

AVAILABLE FINISHES:

23085001



NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations. We reserve the right to make revisions without notice to product specifications. 02-29-2024

Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet,

go to www.grohe.us.

Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



23 085

BAULOOP®



SINGLE HOLE SINGLE-HANDLE S-SIZE BATHROOM FAUCET 1.2 GPM LESS DRAIN

TECHNICAL DATA:

Product Height 5-13/16 in

Product Width 1-3/4 in

Fitting Spout Height 3-3/8 in

Fitting Spout Reach 3-3/4 in

Fitting Handle Height 5-13/16 in

GPM (Min)-GPM (Max) 1.2 GPM

Fitting No of Holes Required 1

