

26 128

EUPHORIA®

260 THERMOSTATIC SHOWER SYSTEM

Pure Freude
an Wasser







STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE TurboStat® compact cartridge with wax thermoelement
- Exposed thermostatic temperature control with SafeStop at 100°F / 38°C
- GROHE SafeStop® Plus optional temperature limiter at 110°F (43°C) included
- 17 1/16" Shower arm
- Switch between hand shower and shower head via built-in diverter
- 2 Discrete functions (non-shared)
- Optional fixed or 45° swivel shower arm
- Bar with adjustable height hand shower holder
- Includes adapters for easy installation (depth adjustable)
- 59" Metal shower hose (28 417)
- Speed Clean® anti-lime system
- Euphoria® 260 shower head (26 457), 2.5gpm
- 3 Adjustable sprays: Rain, SmartRain, Jet
- Euphoria® 110 Duo hand shower (27 238), 2.5gpm
- 2 Spray patterns: Rain, SmartRain
- Optional: EasyReach Accessory Tray (26 362) (sold separately)
- Optional: Spacer Disc 1/4" (27 180) (sold separately)
- Optional: Longer Rail 46" (1166mm) (48 053) (sold separately)
- Optional: Shorter Rail 34" (866mm) (48 054) (sold separately)
- Optional: Service Stop (12 400) (sold separately)





PRODUCT FEATURES:

-  GROHE StarLight®
-  GROHE TurboStat®
-  GROHE DreamSpray®
-  Speed Clean®

CERTIFICATIONS:

- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- CSA B125.1
- ASME A112.18.1

AVAILABLE FINISHES:

- 26128001**  GROHE StarLight® Chrome
- 26128EN1**  Brushed Nickel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.630.582.7711 Fax: 1.630.582.7722
We reserve the right to make revisions without notice to product specifications.
For the most current Specification Sheet, go to www.grohe.us.
10-20-2021

PART OF **LIXIL**

26 128

EUPHORIA®

260 THERMOSTATIC SHOWER SYSTEM

*Pure Freude
an Wasser*



TECHNICAL DATA:

Product Height	45-15/17 in
Product Length	23-11/16 in
Product Width	11-3/4 in
GPM (Min)-GPM (Max)	2.5 gal (US)/min

