28 417

ROTAFLEX

59" METAL LONGLIFE TWIST-FREE SHOWER HOSE



STANDARD SPECIFICATION:

- GROHE StarLight®
- 59" Long
- · Metal hose
- Tensile strength 500 N
- Pressure resistance: up to 14.5psi (16 bar)
- Heat resistance 165°F
- AntiFold bend proof
- 1/2" NPT female threads
- Rotation cone for Twist-free function
- Silicone strip prevents hand shower from turning while in body pray position



PRODUCT FEATURES:



GROHE StarLight®

CERTIFICATIONS:



- · Massachusetts Plumbing Board Approved
- CSA B125.1
- ASME A112.18.1

AVAILABLE FINISHES:

GROHE StarLight® 28417000 Chrome Hard Graphite 28417A00 Polished Nickel 28417BE0 InfinityFinish™ **Brushed Nickel** 28417EN0 InfinityFinish™ Brushed 28417GN0 Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.



28 417

ROTAFLEX



59" METAL LONGLIFE TWIST-FREE SHOWER HOSE

TECHNICAL DATA:

Product Height 7/8 in

Product Length 59-1/16 in

Product Width 7/8 in

