











Product Description:

Digital Controller

Standard Specification:

- Including digital thermostat unit
- Includes digital controller (intuitive multi-functional operating unit)
- Wireless technology
- Temperature and flow control
- Pause-function
- Memory-function
- LED-ring incl. warming-up function: visual feedback when preferred temperature is reached
- Digital thermostat unit (concealed body)
- Warm/cold 1/2" supplies
- 1 x 1/2" outlet
- Transceiver unit for Digital Controller and Digital thermostat unit incl. 9.8 ft. cable
- GROHE TurboStat digital controlled compact cartridge with wax thermoelement
- Default setting configurable during installation: automatic safety shut-off after 20 min
- Automatic safety shut-off after 20 min
- GROHE StarLight chrome finish
- **GROHE EcoJoy** technology for less water and perfect flow Requires:
- Requires Hardwire Power Supply (36 078 000) or Plug-In Power Supply (65 912 000)
- 13.4 gpm at 45psi
- Includes a 12" Digital gateway for optimal installation reach
- Includes three 3V lithium batteries for digital controller and diverter

Applicable Codes & Standards:

- Energy Policy Act of 1992
- ASME A112.18.1/CSA B125.1
- US Federal and State material regulations

Color:

□ 36294000 StarLight Chrome