



The Safety Tubs 52" x 30" Gelcoat walk-in bath provides a similar bathing experience to larger models but fits in smaller spaces and uses less water. The included tub extender allows this tub to retrofit in the same space as a standard bathtub. The full sized, outward opening, contoured door with a low door threshold allows ease of entry and exit.

Fully equipped, the Premium Series offers all the latest in safety and comfort features and is available with the most advanced therapeutic options and backed by lifetime warranty on the door seal, a 10 year warranty on the tub shell and a 5 year warranty on all other components.

Experience a soft and caressing

Jet Massage



A soothing and invigorating water jet massage system, the Jet Massage features an in-line heater, an automatic tub cleaning system and Legs-Only massage. Customize back and leg muscle therapies with 12 different water jets. The Jet Massage is combined with all of the features of the Soaker Tub providing an enhanced therapeutic bathing experience.

Air Massage



all-over body massage powered by a variable speed heated blower that releases thousands of air bubbles rising throughout the water from 26 different air jets. The automatic purge cycle helps keep the system running efficient and clean. The Air Spa is combined with all of the features of the Soaker Tub providing an enhanced therapeutic bathing experience.

Dual Massage System





Combines all of the features of the Soaker Tub, the Air Massage and the Jet Massage Systems for the ultimate therapeutic bathing experience.

Minute Drain® System



Spend less time waiting with this patented innovation, that requires no additional plumbing, once activated it rapidly pumps the water out from within the tub-making it safe to open the door and exit the tub. Included in all systems.

SSOD5230 PREMIUM SERIES 52" X 30" WALK-IN BATH

SSOD5230XS-XX Soaking Tub

- Tub Extender Kit to fill 60" space
- Available in White or Biscuit and in Left Hand or Right Hand Door/Drain Configuration
- Outward opening door with watertight door system with a lifetime warranty on the door seal
- · Built-in chair height seat
- · Polished chrome trim and cable driven waste and overflow
- · Built-in safety bar and textured tub floor
- Patented Minute Drain[®] fast water removal system
- · Premium fast-fill tub faucet and handheld showering wand
- · Partial seat transfer

SSOD5230XJ-XX Jet Massage System Combines all of the features of the Soaking Tub, plus:

- · Jetted in-line heater
- 12 massage jets with variable flow
- · Legs-only massage
- Self-cleaning sanitation system


SSOD5230XD-XX Air Massage System Combines all of the features of the Soaking Tub, plus:


- Variable speed heated blower
- · 26 seat and floor air injectors
- · Automatic purge cycle

SSOD5230XD-XX Dual System

Combines all of the features of the Soaker Tub, the Jet Massage and the Air Massage Systems for the ultimate therapeutic bathing experience, plus:

 Multi-colored light system positioned at the bottom of the bath that creates a peaceful bathing experience





0=::=:::::= 0: = 0::	ICATIONS FOR SSODS2SUXX-XX		
WALK-IN BATHTUB			
INSTALLED SIZE	52 x 30 x 40 ln. (1320 x 762 x 1016mm)		
WEIGHT	155 Lbs. (70 Kg.)		
WEIGHT w/WATER	781 Lbs. (354 Kg.)		
OPERATING GALLON	75 Gal. (284 L.)		
FLOOR LOADING	73 Lbs./Sq. Ft. (356 Kgs/Sq. m.)		
(PROJECTED AREA)			
CUBE (FT ³)	36.1		

CENEDAL CRECIEICATIONS FOR SCORESZOVY VV

To Be Specified - Required:

☐ Drain Configuration: Left (L) or Right (R)

☐ Color: White (WH) or Biscuit (BC)

Options:

☐ Handshower Glide Bar: 9HSB☐ 24 inch Grab Bar: 9GB-24

☐ Neck Rest: 9NR



Notes: The jetted heater is designed to maintain water temperature during operation. It will not heat cold water to desired bathing temperature. Tub is supported by the frame and five integrated adjustable feet, no additional support required. Refer to installation instructions supplied with tub for additional information. Provide suitable reinforcement to sub floor for all supports.

Our products are in compliance with the following codes: Uniform Plumbing Code UPC*; National Plumbing Code of Canada; International Plumbing Code IPC*

Our products conform to the following standards: ASME A112.19.7, ASME A112.19.15; CSA B45, CSA B45.5; CSA C22.2 No. 218.2; UL-1795; ANSI Z124.1.2 Our products are listed with: c ETL us

IMPORTANT: Dimensions of fixtures are nominal, may vary and are subject to change or cancellation. No responsibility is assumed for use of superseded or voided leaflet.

