

10 306 6

RAINSHOWER™

2-HANDLE THERMOSTATIC DUAL FUNCTION SHOWER BUNDLE

Pure Freude
an Wasser



STANDARD SPECIFICATION:

- GROHE StarLight®
- GrohTherm® Dual Function 2-Handle Thermostatic Valve Trim (24 133)
- GROHE TurboStat® compact ¾" cartridge with wax thermo element
- GROHE SafeStop safety button with manual override at 100°F/38°C
- GROHE AquaDimmer (Top handle) includes integrated shut off & 2-way diverter (2 discrete functions)
- GrohTherm® Rapido SmartBox (35 601)
- Rainshower™ 310 Mono 12" (310 mm) Shower Head (26 569) Spray: PureRain. Max. Flow Rate: 6.6 L/min (1.75 gpm)
- Rainshower™ 15" (381 mm) Shower Arm (28 540)
- Rainshower™ 24" (610 mm) Shower Slide Bar (26 602)
- Rainshower™ SmartActive Hand Shower (26 545) Spray: Rain, Jet, ActiveMassage. Max. Flow Rate: 6.6 L/min (1.75 gpm)
- Metal Shower Hose 1500 (59") (26 994)
- Rainshower™ Wall Union (26 635) with ½" NPT threads



PRODUCT FEATURES:



GROHE StarLight®



GROHE TurboStat®

CERTIFICATIONS:



- CEC Certified
- CALGreen Compliant
- CSA B125.1
- ASME A112.18.1

AVAILABLE FINISHES:

1030660000



GROHE StarLight® Chrome

1030662430



Matte Black

103066GN00



Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.888.644.7643 Fax: 1.905.366.2071

We reserve the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.grohe.ca.

02-05-2024

PART OF LIXIL

