

10 307 0

## RAINSHOWER™

# SMARTCONTROL® THERMOSTATIC DUAL FUNCTION SHOWER BUNDLE

Pure Freude  
an Wasser



### STANDARD SPECIFICATION:

- GROHE StarLight®
- GrohTherm® SmartControl® Dual Function Thermostatic Valve Trim (29 137)
- GROHE SmartControl®: push for ON-OFF, turn for volume adjustment from EcoJoy™ to Full Flow, exchangeable symbols
- GROHE TurboStat® compact 3/4" cartridge with wax thermo element
- GROHE SafeStop safety button with manual override at 100°F/38°C
- Multiple outlets can be run simultaneously
- GrohTherm® Rapido SmartBox (35 601)
- Rainshower™ 310 Mono 12" (310 mm) Shower Head (26 569) Spray: PureRain. Max. Flow Rate: 6.6 L/min (1.75 gpm)
- Rainshower™ 15" (371 mm) Shower Arm (28 540)
- Rainshower™ 24" (610 mm) Shower Slide Bar (26 602)
- Rainshower™ SmartActive Hand Shower (26 545) Spray: Rain, Jet, ActiveMassage. Max. Flow Rate: 6.6 L/min (1.75 gpm)
- Metal Shower Hose 1500 mm (59") (26 994)
- Rainshower™ Wall Union (26 635) with 1/2" NPT threads






### PRODUCT FEATURES:

-  GROHE StarLight®
-  GROHE SmartControl®
-  GROHE TurboStat®
-  GROHE EcoJoy™

### CERTIFICATIONS:

- CSA B125.1
- ASME A112.18.1

### AVAILABLE FINISHES:

-  1030700000 GROHE StarLight® Chrome
-  1030702430 Matte Black
-  103070GN00 Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.888.644.7643 Fax: 1.905.366.2071  
We reserve the right to make revisions without notice to product specifications.  
For the most current Specification Sheet, go to [www.grohe.ca](http://www.grohe.ca).  
02-06-2024

PART OF LIXIL

10 307 0

# RAINSHOWER™

## SMARTCONTROL® THERMOSTATIC DUAL FUNCTION SHOWER BUNDLE

Pure Freude  
an Wasser



### TECHNICAL DATA:

