24 107

GROHTHERM

SINGLE FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM WITH CONTROL MODULE



STANDARD SPECIFICATION:

- GROHE StarLight
- GROHE TurboStat compact cartridge with wax thermoelement
- Thermostatic temperature control with GROHE SafeStop safety button at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- Volume control with ceramic disc stop valve, 120°
- 6 1/4" Metal wall trim plate with GROHE QuickFix (concealed mounting screws)
- Metal trim angle adjustable up to 6°
- Upper handle includes integrated volume control and On/Off
- ADA compliant lever handles
- Includes service stops
- 7.1gpm at 45psi
- Thermal Disinfection: Can handle hot water up to 180° F (82°C) for 5 minutes
- Requires GROHE Rapido SmartBox (35 601 000) (sold separately)



PRODUCT FEATURES:



GROHE QuickFix

GROHE TurboStat

CERTIFICATIONS:

- Massachusetts Plumbing Board Approved
- N/A
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.10.1

AVAILABLE FINISHES:

24107000 GROHE StarLight Chrome **241072430** Matte Black

24107A00 Hard Graphite

24107EN0 Brushed Nickel InfinityFinish

24107GN0 Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations. We reserve the right to make revisions without notice to product specifications. 06-12-2024

US Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us.

Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.




GROHTHERM Single Function 2-Handle Thermostatic Trim MODEL # 24107EN0















Product Description: GROHTHERM

Single Function 2-Handle Thermostatic Trim

Standard Specification:

- Required rough-in-set sold separately (GROHE Rapido SmartBox 35 601 000)
- GROHE TurboStat Compact cartridge with wax thermoelement
- GROHE StarLight finish
- Wall trim plate with GROHE QuickFix (Concealing mounting screws)
- Metal trim angle adjustable up to 6°
- Thermostatic temperature control with SafeStop at 100° E/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- Volume control with ceramic stop valve, 120°

Applicable Codes & Standards:

- Energy Policy Act of 1992
- ASME A112.18.1/CSA B125.1
- ICC/ANSI A117.1
- LOGO CEC

Color:

□ 24107EN0 Brushed Nickel InfinityFinish

24 107

GROHTHERM

Pure Freude an Wasser GROHE

SINGLE FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM WITH CONTROL MODULE

TECHNICAL DATA:

Product Height 158 mm

Product Length 43 mm

Product Width 158 mm

