

105349

CUBEO

SINGLE HOLE SINGLE HANDLE S-SIZE
BATHROOM FAUCET, COLD START,
1.2 GPM (4.5L/MIN)

*Pure Freude
an Wasser*



STANDARD SPECIFICATION:

- GROHE StarLight® maintains luster on brushed and polished finishes
- GROHE Silkmove® Durable ceramic cartridge features a ceramic disc mixing valve and a ceramic balancing spool
- GROHE EcoJoy® uses less water without sacrificing performance
- Faucet Height: 5-7/8"
- Spout Reach: 4-3/16"
- Aerator Height: 3-3/8"
- Valve turns on and off in the cold position (right up to mid position) to reduce hot water use and conserve energy
- To activate hot water, turn the lever to the left of the mid position
- Metal body and handle
- 1.2 gpm (4.5 L/min) meets WaterSense Requirements, Can handle Thermal Disinfection cycle of 82C for 30 minutes, Supply lines and push pop drain included
- Lift rod drain

PRODUCT FEATURES:



GROHE StarLight®



GROHE SilkMove®



GROHE EcoJoy®

CERTIFICATIONS:

- IAPMO (cUPC)
- EPA Watersense
- State of Massachusetts

COMPLIES WITH:

- ASME A112.18.1/CSA B125.1
- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372

AVAILABLE FINISHES:

1053490000 CHROME

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 1-15-2025

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF LIXIL

105349

CUBEO

SINGLE HOLE SINGLE HANDLE S-SIZE
BATHROOM FAUCET, COLD START,
1.2 GPM (4.5L/MIN)

*Pure Freude
an Wasser*



TECHNICAL DATA:

Product Height	7-3/16 in
Product Length	4-3/16 in
Product Width	1-7/8 in
Fitting Spout Height	3-3/8 in
Fitting Spout Reach	5 in
Fitting Handle Height	5-7/8 in
GPM (Min)-GPM (Max)	1.2 gal (US)/min
Fitting No of Holes Required	1

