

#### FEATURES:

- **Touchless operation** limits the spread of germs for a safer restroom
- **CR-P2 lithium battery** preinstalled in the faucet
- **Battery Life:** 6 years @ 4,000 uses per month
- **Above-Deck Mixing:** Allows user to manually adjust temperature. Adjustable hot limit stop. Red & blue indicators.
- **Removable Mixing Handle:** Installer can set temperature and remove handle to prevent user adjustment. Cover plug included.
- **Dual Inlets:** For hot and cold water. Check valves included to prevent cross flow. Filter assemblies protect the solenoid valve from debris.
- **Clean, Integrated Design:** All electronics contained in faucet spout. No control box below deck.
- **Easy Installation & Maintenance:** Faucet installs from the top. All serviceable parts are easily accessible.
- **Flexible Selectronic® Platform** with programmable sensor and interchangeable power supplies.
- **Self-Cleaning Solenoid Reduces Maintenance:** Integral wiper spring prevents clogging and run-on. Silicon seals.
- **Adjustable Range:** Detection zone can be adjusted manually or with optional remote control.
- **Fail-Safe:** Faucet automatically shuts off upon loss of power or dead battery. No reset required.
- **Optional Remote Control Allows for Customization**
  - **Auto Purge:** Periodically purges stagnant water from faucet and supply lines. Frequency and duration are adjustable.
  - **Safety Timer:** Turns water off if the sensor is blocked for 55 seconds. Timing is adjustable.
- **Lead-Free:** Faucet contains ≤ 0.25% total lead content by weighted average.

#### MODEL NUMBER:

##### ■ DC POWERED

- ❑ **7766203** 0.35 gpm pressure compensating, vandal-resistant multi-laminar spray.
- ❑ **7766205** 0.5 gpm pressure compensating, vandal-resistant multi-laminar spray.
- ❑ **7766215** 1.5 gpm pressure compensating, vandal-resistant laminar flow outlet with adjustable spray face.



##### ■ OPTIONAL 4" and 8" Deck Plates

- ❑ **706P400** 4" metal deck plate with 1/4" fixation studs and quick spin nuts. Includes fixation screw that prevents the spout from rotating.
- ❑ **706P800** 8" metal deck plate with 1/4" fixation studs and quick spin nuts. Includes fixation screw that prevents the spout from rotating.

##### ■ OPTIONAL Remote Control

- ❑ **605XRCW** Remote control adjusts setup parameters and allows for customization of functions. Can be used to program all Selectronic faucets and flush valves.

#### DESCRIPTION:

Deck-mount electronic faucet with touchless operation. Integrated design with sensor, solenoid valve and electronics enclosed in the spout. Above-deck mixing with hot limit safety stop and red / blue indicators. Water pressure range from 20 - 120 psi. Vandal-resistant single-post mounting. Dual inlets for hot and cold water. Pre-installed 24" flexible inlet hoses with filter assembly and 3/8" compression fitting.

#### RECOMMENDED SPECIFICATION:

Electronic, sensor-operated lavatory faucet shall feature a programmable sensor and an electronically operated self-cleaning solenoid valve with chemical resistant silicon seals. Integrated design with all electronics enclosed in the spout. Features above deck mixing with hot limit safety stop and red / blue indicators. Shall also feature a vandal resistant metal body with single-post mounting. Shall meet ANSI A112.18.1 and ANSI 117.1 codes. Model shall be American Standard # 77662\_\_\_.002

## CODES AND STANDARDS




These products meet or exceed the following codes and standards:

**ANSI A117.1**  
**ASME A112.18.1/CSA B125.1**  
**NSF/ANSI/CAN 372**  
**NSF/ANSI/CAN 61**

**ADA** MEETS THE AMERICAN DISABILITIES ACT GUIDELINES AND  
**ANSI A117.1** REQUIREMENTS FOR ACCESSIBLE AND  
 USABLE BUILDING FACILITIES-CHECK LOCAL CODES

FINISHES:	
Polished Chrome	.002
Brushed Nickel	.295
*Matte Black	.243
*Brushed Cool Sunrise	.GN0

\*Finish available only in 0.5gpm



PART OF **LIXIL**