

## FEATURES:

- **CR-P2 lithium battery** preinstalled in the faucet
- **Battery Life:** 6 years @ 4,000 uses per month
- **Hygienic, touch-free operation**
- **Clean, Integrated Design:** All electronics contained in faucet spout. No control box below deck.
- **Easy Installation & Maintenance:** Faucet installs from the top. All serviceable parts are easily accessible.
- **Flexible Selectronic® Platform** with programmable sensor and interchangeable power supplies.
- **Self-Cleaning Solenoid Reduces Maintenance:** Integral wiper spring prevents clogging and run-on. Silicon seals.
- **Adjustable Range:** Detection zone can be adjusted manually or with optional remote control.
- **Fail-Safe:** Faucet automatically shuts off upon loss of power or dead battery. No reset required.
- **Single Inlet:** For cold or tempered water. Filter assembly protects the solenoid valve from debris.
- **Optional Remote Control Allows for Customization**
  - **Auto Purge:** Periodically purges stagnant water from faucet and supply lines. Timing is adjustable with optional remote control.
  - **Safety Timer:** Turns water off if the sensor is blocked for 55 seconds. Timing is adjustable with optional remote control.
- **Lead-Free:** Faucet contains  $\leq 0.25\%$  total lead content by weighted average.

## MODEL NUMBER:

### ■ DC POWERED

- ☐ **7037103** 0.35 gpm pressure compensating, vandal-resistant multi-laminar spray.
- ☐ **7037105** 0.5 gpm pressure compensating, vandal-resistant multi-laminar spray.

### ■ OPTIONAL 4" and 8" Deck Plates

- ☐ **703P400** 4" metal deck plate with 1/4" fixation studs and quick spin nuts. Includes fixation screw that prevents the spout from rotating.
- ☐ **706P800** 8" metal deck plate with 1/4" fixation studs and quick spin nuts. Includes fixation screw that prevents the spout from rotating.

### ■ OPTIONAL Remote Control

- ☐ **605XRCW** Remote control adjusts setup parameters and allows for customization of functions. Can be used to program all Selectronic faucets and flush valves.

## DESCRIPTION:

Deck-mount electronic faucet with proximity operation. Integrated design with sensor, solenoid valve and electronics enclosed in the spout. Water pressure range from 20 - 120 psi. Vandal-resistant single-post mounting. Single inlet for cold or tempered water. Pre-installed 24" flexible inlet hose with filter assembly and 3/8" compression fitting.

## RECOMMENDED SPECIFICATION:

Electronic, sensor-operated lavatory faucet shall feature a programmable sensor and an electronically operated self-cleaning solenoid valve with chemical resistant silicon seals. Shall feature an integrated design with all electronics enclosed in the spout. Shall also feature a vandal resistant metal body with single-post mounting. Shall meet ANSI A112.18.1 and ANSI 117.1 codes. Model shall be American Standard # 70371\_\_002

### CODES AND STANDARDS

These products meet or exceed the following codes and standards:

**ANSI A117.1**

**ASME A112.18.1/CSA B125.1**

**NSF/ANSI/CAN 372**




**NSF/ANSI/CAN 61**

**ADA** MEETS THE AMERICAN DISABILITIES ACT GUIDELINES AND  
**ANSI A117.1** REQUIREMENTS FOR ACCESSIBLE AND  
USABLE BUILDING FACILITIES-CHECK LOCAL CODES

#### FINISHES:

Polished Chrome	.002
Brushed Nickel	.295
*Matte Black	.243
*Brushed Cool Sunrise	.GN0

\*Finish available only in 0.5gpm



PART OF LIXIL