

## Technical Data Sheet

|                              |                        |                        |
|------------------------------|------------------------|------------------------|
| 1. Collection                | FABE                   |                        |
| 2. Category of tile          | All Glazed tile        | All Unglazed tile      |
| 3. Length, Width & Thickness | 227.0 x 60.0 x 11.0 mm | 227.0 x 60.0 x 11.0 mm |
| 4. Item number               | FABN-2/21N~27N         | FABN-2/105N~109N       |

| characteristics                      |        | JIS A 5209       | JIS A 5209       |
|--------------------------------------|--------|------------------|------------------|
| Length (mm)                          |        | 227.0 ± 3.0      | 227.0 ± 3.0      |
| Width (mm)                           |        | 60.0 ± 2.0       | 60.0 ± 2.0       |
| Crook (mm)                           | Length | ≤ 3.0            | ≤ 3.0            |
|                                      | Width  | ≤ 2.0            | ≤ 2.0            |
| Thickness (mm)                       |        | 11.0 ± 1.5       | 11.0 ± 1.5       |
| Centre curvature (mm)                |        | ± 2.0            | ± 2.0            |
| Torsion (mm)                         |        | ≤ 1.5            | ≤ 1.5            |
| Edge curvature (mm)                  |        | N/A              | N/A              |
| Straightness of sides (mm)           |        | ± 2.0            | ± 2.0            |
| Rectangularity (mm)                  |        | ≤ 2.0            | ≤ 2.0            |
| Shape of back feet                   |        | Dovetailed shape | Dovetailed shape |
| Height of back feet (mm)             |        | 1.5 - 3.5        | 1.5 - 3.5        |
| Water absorption (%) (Vacuum method) |        | ≤ 10.0           | ≤ 10.0           |
| Breaking strength (N)                |        | ≥ 720            | ≥ 720            |
| Thermal shock resistance             |        | N/A              | N/A              |
| Crazing resistance                   |        | No crazing       | N/A              |
| Frost resistance                     |        | No damage        | No damage        |
| Resistance to chemicals              |        | Declared value   | Declared value   |

850780

Note :

Testing methods are in compliance with JIS A5209:2020 and JIS A 1509.