

## Technical Data Sheet

1. Collection	RHYTHMIC II	
2. Category of tile	BI Unglazed tile	
3. Length, Width & Thickness	225.5 x 19.5 x 10.0 mm	70.5 x 19.5 x 13.0 mm
4. Item number	HAL-20B/RYS-1~RYS-3	

characteristics		JIS A 5209	JIS A 5209
Length (mm)		225.0 ± 2.4	70.5 ± 1.2
Width (mm)		19.5 ± 0.8	19.5 ± 0.8
Crook (mm)	Length	≤ 1.4	≤ 1.4
	Width	≤ 1.0	≤ 1.0
Thickness (mm)		10.0 ± 1.2	13.0 ± 1.2
Centre curvature (mm)		N/A	± 0.9
Torsion (mm)		N/A	≤ 0.7
Edge curvature (mm)		N/A	N/A
Straightness of sides (mm)		± 1.6	± 0.8
Rectangularity (mm)		N/A	N/A
Shape of back feet		N/A	N/A
Height of back feet (mm)		N/A	N/A
Water absorption (%) (Vacuum method)		≤ 3.0	≤ 3.0
Breaking strength (N)		≥ 540	≥ 540
Thermal shock resistance		N/A	N/A
Crazing resistance		N/A	N/A
Frost resistance		No damage	No damage
Resistance to chemicals		Declared value	Declared value

850780

Note :

1. Testing methods are in compliance with JIS A5209:2020 and JIS A 1509.
2. Manufacture a unit by combining tiles of 2 different shapes.