

## Technical Data Sheet

1. Collection	SENTOUSAI		
2. Category of tile	BI Unglazed tile		
3. Length, Width & Thickness	235.0 x 13.0 x 13.0 (Max) mm	235.0 x 13.0 x 17.0 (Max) mm	235.0 x 13.0 x 22.0 (Max) mm
4. Item number	HAL-RN/STS-11-STS-15		

characteristics		JIS A 5209	JIS A 5209	JIS A 5209
Length (mm)		235.0 ± 2.4	235.0 ± 2.4	235.0 ± 2.4
Width (mm)		13.0 ± 0.8	13.0 ± 0.8	13.0 ± 0.8
Crook (mm)	Length	≤ 2.0	≤ 2.0	≤ 2.0
	Width	≤ 1.0	≤ 1.0	≤ 1.0
Thickness (mm)		Specified by the manufacturer	Specified by the manufacturer	Specified by the manufacturer
Centre curvature (mm)		N/A	N/A	N/A
Torsion (mm)		N/A	N/A	N/A
Edge curvature (mm)		N/A	N/A	N/A
Straightness of sides (mm)		± 1.6	± 1.6	± 1.6
Rectangularity (mm)		N/A	N/A	N/A
Shape of back feet		N/A	N/A	N/A
Height of back feet (mm)		N/A	N/A	N/A
Water absorption (%) (Vacuum method)		≤ 3.0	≤ 3.0	≤ 3.0
Breaking strength (N)		≥ 540	≥ 540	≥ 540
Thermal shock resistance		N/A	N/A	N/A
Crazing resistance		N/A	N/A	N/A
Frost resistance		No damage	No damage	No damage
Resistance to chemicals		Declared value	Declared value	Declared value

850780

### Note :

1. Testing methods are in compliance with JIS A5209:2020 and JIS A 1509.
2. Manufacture a unit by combining tiles of 3 different shapes.
3. Thickness is not specified by JIS because the surface of this shape is rough.