

20586

ALLURE NEW

ALLURE 2-HANDLE WALL MOUNT FAUCET, 1.2 GPM (4.5 L/MIN)










GROHE SPA

STANDARD SPECIFICATION:

- GROHE LongLife finish
- GROHE EcoJoy
- Wall mount
- 8 1/2" Spout reach
- Precision temperature control with haptic click feedback on handles (optional upon installation, included)
- Requires vessel rough-in valve (33 885 000) (sold separately)
- Requires sink push pop drain with overflow (48 656) or without overflow (48 657) (sold separately)



AVAILABLE FINISHES:

- | | | |
|-----------|---|-------------------------------|
| 20586001 |  | GROHE StarLight Chrome |
| 205862431 |  | Matte Black |
| 20586A01 |  | Hard Graphite |
| 20586AL1 |  | Brushed Hard Graphite |
| 20586DL1 |  | Brushed Warm Sunset |
| 20586EN1 |  | Brushed Nickel InfinityFinish |
| 20586GN1 |  | Brushed Cool Sunrise |

CERTIFICATIONS:



- ADA
- WaterSense
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- NSF 372
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

PRODUCT FEATURES:

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 10-14-2025

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF **LIXIL**

20586

ALLURE NEW

ALLURE 2-HANDLE WALL MOUNT
FAUCET, 1.2 GPM (4.5 L/MIN)



GROHE SPA

TECHNICAL DATA:

Product Height

Fitting Spout Reach 8-1/2 in

GPM (Min)-GPM
(Max) 1.2 GPM

Fitting No of Holes
Required 3

