29178

ALLURE NEW

GROHE SPA

DUAL FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM

STANDARD SPECIFICATION:

- GROHE LongLife finish
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE FastFixation (concealed mounting screws)
- Thermostatic temperature control with GROHE SafeStop safety button at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- Volume control with ceramic disc stop valve, 120°
- Metal trim angle adjustable up to 6°
- Volume control with ceramic disc stop valve, 120°
- Requires Rapido Smartbox Rough-in Valve (35 601) (sold separately)



AVAILABLE FINISHES:

29178001



291782431

Matte B**l**ack

29178A01

Hard Graphite

29178AL1

Brushed Hard Graphite

29178DL1

Brushed Warm Sunset

29178EN1

Brushed Nickel InfinityFinish

29178GN1

Brushed Cool Sunrise

CERTIFICATIONS:



- Massachusetts Plumbing Board Approved
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.1016

PRODUCT FEATURES:



NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 10-21-2025 **Canada**

Tel: 1.630.582.7711 Fax: 1.630.582.7722 For the most current Specification Sheet, go to www.grohe.us.

Canada Tel: 1.888.644.7643 Fax: 1.905.366.2071 For the most current Specification Sheet, go to www.grohe.ca.



29178

ALLURE NEW



DUAL FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM

TECHNICAL DATA:

Product Height 2-3/4 in

Product Width 1-11/16 in

