29178

ALLURE NEW

DUAL FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM

GROHE SPA

STANDARD SPECIFICATION:

- GROHE LongLife finish
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE FastFixation (concealed mounting screws)
- Thermostatic temperature control with GROHE SafeStop safety button at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- Volume control with ceramic disc stop valve, 120°
- Metal trim angle adjustable up to 6°
- Requires Rapido SmartBox Rough-in Valve (35 601) (sold separately)



AVAILABLE FINISHES:

29178001	Chrome
291782431	Matte Black
29178A01	Hard Graphite
29178AL1	Brushed Hard Graphite
29178DL1	Brushed Warm Sunset
29178EN1	Brushed Nickel InfinityFinish
29178GN1	Brushed Cool Sunrise

CERTIFICATIONS:

- CEC Certified
- Massachusetts Plumbing Board Approved
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.1016

PRODUCT FEATURES:

GROHE TurboStat

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 11-19-2026

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet, go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet, go to www.grohe.ca.

PART OF LIXIL

29178

ALLURE NEW

DUAL FUNCTION 2-HANDLE THERMOSTATIC VALVE TRIM

GROHE SPA

TECHNICAL DATA:

Product Height	6 in
Product Width	1-11/16 in

