

107181

RAINSHOWER AQUA

GROHTHERM AQUA TILES 4 OUTLET THERMOSTATIC VALVE



GROHE SPA

STANDARD SPECIFICATION:

- GROHE TurboStat compact cartridge with wax thermoelement
- 4 outlets each top and bottom, 1/2" Female NPT
- Installation Depth 87-117mm
- Leak proof housing
- Optional flow reducer for CALGreen Compliance Included
- Maximum flow performance w/outlets simultaneously running (at 43.5 psi): 12.6gpm/1.8gpm with flow restrictor
- Flow performance for single outlet (at 43.5 psi): 9.7gpm/1.8gpm w/flow restrictor



AVAILABLE FINISHES:

1071810000 No Finish

CERTIFICATIONS:



- Massachusetts Plumbing Board Approved
- ASSE 1016
- CSA B125.1
- CSA B125.16
- ASME A112.18.1
- ASME A112.1016

PRODUCT FEATURES:

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 10-15-2025

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF **LIXIL**

107181

RAINSHOWER AQUA

GROHTHERM AQUA TILES 4 OUTLET THERMOSTATIC VALVE



GROHE SPA

TECHNICAL DATA:

